



PHILIPPINE INSTITUTE FOR DEVELOPMENT STUDIES  
18<sup>th</sup> Floor Three Cyberpod Centris-North Tower EDSA Quezon City  
Tel No. 8877-4013/4006 : Fax 8877-4099 : TIN # 000-844-550

REQUEST FOR QUOTATION

Date: July 17, 2025  
Reference No (PR No.): 2025-204

To All Interested Bidders:

This is to request for quotation on the PIDS procurement requirement enumerated hereunder. If you are interested and, in a position, to furnish the same, we shall be glad to have your best price, terms and conditions of delivery, submitted not later than **July 23, 2025, 05:00 PM** addressed to the *Procurement Management Division of the Administrative and Finance Department* at the abovementioned address. PIDS reserves the right to reject any and all bids, declare failure of bidding, or not award the contract under the conditions specified in Section 41 of the 2016 Revised IRR of RA 9184.

The price quotation/s, to be denominated in Philippine peso, **shall include all applicable taxes, duties, and/or levies payable.**

Very truly yours,

July R. Sunga  
CAO, Procurement Management Division

Item	Qty	Unit	Articles/Description	Unit Cost	Total Cost
1	2	Unit	Monochrome Laserjet Network Printer ABC: Php300,000.00		
Remarks: Please see attached technical specifications					
Requirements: <ul style="list-style-type: none"> <li>Valid Mayor's/Business Permit</li> <li>PhilGEPS Registration No. (if PhilGEPS Platinum Certificate is provided, Mayor's/Business Permit is no longer required)</li> <li>Notarized Omnibus Sworn Statement - Supported by applicable Notarized Authority of Representative/Signatory</li> </ul>					

The price and details of the above offer are certified correct:

_____ Name of Firm ( <i>Bidder</i> )	_____ Signature over Printed Name of <i>Bidder's Representative</i>
_____ Address	_____ Business Permit No.
_____ Telephone <i>and/or</i> Mobile No.	_____ Tax Identification Number ( <i>TIN</i> )
_____ Email Address	_____ PhilGEPS Registration Number

Note: PIDS is evaluating its supplier's performance based on the quality of services rendered or goods delivered, timeliness of delivery, customer/after sales service and overall quality of service.

# **Monochrome LaserJet Network Printer Technical Specifications –**

## **2 Units**

<b>Functions</b>	Print
<b>Print</b>	
Duplex Print Options	Automatic (standard)
Print Speed	<ul style="list-style-type: none"><li>• Black (A4, normal): Up to 71 ppm</li><li>• Black (letter, normal): Up to 75 ppm</li><li>• Black (A4, duplex): Up to 58 ppm</li><li>• Black (letter, duplex): Up to 58 ppm</li></ul>
First Page Out	<ul style="list-style-type: none"><li>• Black (A4, ready): As fast as 5.1 sec.</li><li>• Black (A4, sleep): As fast as 7.9 sec. in mm</li></ul>
Print Technology	Laser
Print Resolution	<ul style="list-style-type: none"><li>• Black (best): Up to 1200 x 1200 dpi</li><li>• Black (normal): FastRes 1200</li><li>• Black (fine lines): Up to 1200 x 1200 dpi</li></ul>
Print Resolution Technology	<ul style="list-style-type: none"><li>• Normal FastRes 1200</li><li>• Fine Lines (1200 x 1200 dpi)</li><li>• Quickview (300 x 300 dpi)</li><li>• Economode (600 x 600 dpi)</li></ul>
Print Cartridges Number	1 (black)
Stand Print Languages	<ul style="list-style-type: none"><li>• PCL 6</li><li>• PCL 5</li><li>• PostScript Level 3 emulation</li><li>• Native PDF printing (v1.7)</li><li>• Mobile printing support</li></ul>
Printer Management	<ul style="list-style-type: none"><li>• Printer Assistant</li><li>• Device Toolbox</li><li>• Web-based management software</li><li>• Security management tools</li><li>• SNMP Proxy Agent</li><li>• Web Services Proxy Agent</li><li>• Administrator Resource Kit for Universal Print Driver (Driver Configuration Utility, Driver Deployment Utility, Managed Printing Administrator)</li></ul>
<b>Connectivity</b>	
Standard Connectivity	<ul style="list-style-type: none"><li>• 1 Hi-Speed USB 2.0 Device port</li><li>• 2 Hi-Speed USB 2.0 Host ports</li><li>• 1 Gigabit Ethernet 10/100/1000T network port</li><li>• 1 Hardware Integration Pocket</li></ul>
Mobile Printing Capability	<ul style="list-style-type: none"><li>• Email-based printing</li><li>• Mobile printing support</li><li>• Cloud print compatibility</li><li>• Mopria™ Certified</li><li>• Remote printing functionality (Optional)</li></ul>
Network Capabilities	<ul style="list-style-type: none"><li>• Embedded Ethernet print server (standard)</li><li>• Supports 10Base-T, 100Base-Tx, 1000Base-T</li><li>• 802.3az Energy Efficient Ethernet for Fast Ethernet and Gigabit links</li><li>• IPsec support (standard)</li></ul>
Memory	<ul style="list-style-type: none"><li>• Standard: 512 MB</li><li>• Maximum: 1.5 GB Max memory, when 1GB Accessory DIMM is installed</li></ul>
Processor Speed	1.2 GHz
Duty Cycle (Monthly)	Up to 300,000 pages; Recommended monthly page volume13: 5000 to 30,000

Paper Handling	
Input	100-sheet multipurpose feeder, 550-sheet input feeder
Output	500 sheet output bin
Media Types	<ul style="list-style-type: none"> <li>• Plain paper</li> <li>• Light paper</li> <li>• Bond paper</li> <li>• Recycled paper</li> <li>• Heavy paper</li> <li>• Extra heavy paper</li> <li>• Cardstock</li> <li>• Pre-printed paper</li> <li>• Pre-punched paper</li> <li>• Colored paper</li> <li>• Rough paper</li> <li>• Heavy rough paper</li> <li>• Monochrome transparency</li> <li>• Labels</li> <li>• Letterhead</li> <li>• Envelopes</li> <li>• Heavy envelopes</li> </ul>
Media Weight	<ul style="list-style-type: none"> <li>• Tray 1: 60 to 200 g/m<sup>2</sup></li> <li>• Automatic Duplexer: 60 to 120 g/m<sup>2</sup></li> </ul>
Media Sizes Custom	<ul style="list-style-type: none"> <li>• 100-sheet multipurpose Tray 1: 76 x 127 to 216 x 356 mm</li> <li>• 550-sheet input Tray 2: 99 x 148 to 216 x 356 mm</li> <li>• 550-sheet optional feeder: 99 x 148 to 216 x 356 mm</li> <li>• 75-sheet envelope feeder: 90 x 148 to 178 x 254 mm</li> </ul>
Dimensions (W x D x H)	431 x 466 x 380 mm
Weight	At most 21.6 kg.
Systems	
Compatible Operating Systems	At least Windows 10, 11, macOS
Security Management	<ul style="list-style-type: none"> <li>• <b>Identity Management:</b> Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional advanced authentication solutions (e.g., badge readers).</li> <li>• <b>Network Security:</b> IPsec/firewall with certificate-based and pre-shared key authentication; Kerberos support; 802.1X authentication (EAP-PEAP, EAP-TLS); SNMPv3; HTTPS; certificate-based access control; Access Control Lists.</li> <li>• <b>Data Security:</b> Storage encryption; encrypted PDF and email using FIPS 140-validated cryptographic libraries; secure erase; SSL/TLS (HTTPS); encrypted credentials.</li> <li>• <b>Device Security:</b> Security lock slot; USB port disablement; hardware integration pocket for third-party security modules; intrusion detection with embedded runtime monitoring for attacks; secure boot with BIOS integrity checking and self-healing; whitelisting to allow only authorized code (DLLs, EXEs, etc.).</li> <li>• <b>Security Management:</b> Compatible with enterprise security management tools; device security logs can be processed by SIEM platforms such as ArcSight and Splunk.</li> </ul>
Fonts and Typefaces	<ul style="list-style-type: none"> <li>• 5 internal scalable TrueType fonts for PCL</li> <li>• 92 internal scalable fonts for PostScript Level 3 emulation (includes Euro symbol)</li> <li>• 1 internal Unicode font (Andale Mono WorldType)</li> <li>• Optional font and IPDS emulation available through external sources</li> </ul>
Control Panel	<ul style="list-style-type: none"> <li>• 4.3-inch (10.92 cm) color touchscreen display</li> <li>• Rotating (adjustable angle) display</li> <li>• Home button</li> </ul>
Display	<ul style="list-style-type: none"> <li>• 4.3-inch (10.92 cm) color touchscreen display</li> <li>• Rotating (adjustable angle) display</li> </ul>
Energy Efficiency Compliance	<ul style="list-style-type: none"> <li>• ENERGY STAR® qualified</li> <li>• Blue Angel certified</li> </ul>

	<ul style="list-style-type: none"> <li>• EPEAT® Silver registered</li> <li>• CECP compliant</li> </ul>
Power	<p><b>Power supply type:</b> Built-in 115V or 220V power supply (not dual voltage; varies by model or configuration code).</p> <p><b>Input voltage:</b></p> <ul style="list-style-type: none"> <li>• 100V–127V nominal <math>\pm 10\%</math> (min 90V, max 140V); 50–60Hz <math>\pm 3</math>Hz (min 47Hz, max 63Hz), 12 A</li> <li>• 220V–240V nominal <math>\pm 10\%</math> (min 198V, max 264V); 50–60Hz <math>\pm 3</math>Hz (min 47Hz, max 63Hz), 6 A</li> </ul> <p><b>Power consumption:</b></p> <ul style="list-style-type: none"> <li>• 877 watts (printing)</li> <li>• 14.98 watts (ready)</li> <li>• 4.28 watts (sleep)</li> <li>• &lt; 0.1 watts (auto-off/manual-on)</li> <li>• &lt; 0.1 watts (manual off)</li> </ul> <p><b>Typical Electricity Consumption (TEC):</b></p> <ul style="list-style-type: none"> <li>• Blue Angel: 3.106 kWh/week</li> <li>• Energy Star: 0.866 kWh/week</li> </ul>
Acoustics	<ul style="list-style-type: none"> <li>• Acoustic Power Emissions (active/printing): 7.1 B(A)</li> <li>• Acoustic Power Emissions (ready mode): Inaudible</li> <li>• Acoustic Pressure Emissions for Bystander (active/printing): 56 dB(A)</li> <li>• Acoustic Pressure Emissions for Bystander (ready mode): Inaudible</li> </ul>
Environmental Ranges	<ul style="list-style-type: none"> <li>• Operating temperature range: 10 to 32.5 °C</li> <li>• Recommended operating temperature: 15 to 27 °C</li> <li>• Operating humidity range: 10 to 80% RH</li> <li>• Recommended operating humidity range: 30 to 70% RH</li> </ul>
Safety Approvals and Requirements	<ul style="list-style-type: none"> <li>• IEC 60950-1:2005 + A1:2009 + A2:2013 (International safety standard)</li> <li>• EN 60825-1:2014 / IEC 60825-1:2014 (Class 1 Laser Product)</li> <li>• EN 62479:2010 / IEC 62479:2010 (RF exposure assessment)</li> <li>• Low Voltage Directive 2014/35/EU with CE Mark (Europe)</li> <li>• GS Certification (Europe)</li> <li>• UL/cUL Listed and UC CoC (United States/Canada)</li> <li>• CAN/CSA C22.2 No. 60950-1-07 (Canada)</li> <li>• Compliance with laser safety standards 21 CFR 1040.10 and 1040.11 (with Laser Notice No. 50)</li> <li>• Other country-specific safety approvals as applicable</li> </ul>
Supported Network Protocols	<ul style="list-style-type: none"> <li>• Supported network protocols: TCP/IP, IPv4, IPv6</li> <li>• Print protocols: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2.0, FTP Print, cloud print compatibility</li> <li>• Discovery protocols: SLP, Bonjour, Web Services Discovery</li> <li>• IP configuration: IPv4 (BootP, DHCP, AutoIP, Manual, TFTP Config, ARP-Ping), IPv6 (Stateless Link-Local, Router-based, DHCPv6)</li> <li>• Management protocols: SNMPv2/v3, HTTP/HTTPS, Telnet, TFTP Config, FTP firmware download, Syslog</li> <li>• Security features: SNMPv3, SSL certificate management, firewall, access control lists (ACL), 802.1x authentication</li> </ul>
Warranty	<ul style="list-style-type: none"> <li>• The warranty includes at least one year of parts and labor, as well as one year of onsite support for ALL parts of the package, both internal and external.</li> <li>• Must include phone support during business hours.</li> <li>• A temporary replacement unit or replacement of defective part(s) should be provided within 24 hours if the unit cannot be repaired within one working day.</li> </ul>

**Total estimated price: ₱150,000.00/unit**